



Weatherproof Exit Enclosure – BR3-EXHS

**BR3-EXHS Weatherproof Exit Enclosure is an IP65 rated weatherproof unit designed to house externally located Ecoglo HYUx.2 and HYUx.3 hybrid signs (sold separately). Protects the sign from the elements so that it continues to operate in all weather conditions.**

## COMPOSITION

The enclosure unit is manufactured from non-corrosive polycarbonate.

## SPECIFICATIONS

IP Rating - IP65

Nominal Voltage - 240V

Nominal Frequency (Hz) - 50Hz

Rated Maximum Ambient Temperature - 40°C

Dimensions - 430mm (L) x 155mm (W) x 231 (D)

## INSTALLATION

The BR3-EXHS enclosure unit must be installed by a qualified electrician strictly in accordance with the Ecoglo installation instructions.

The enclosure unit is suitable for cantilever/flag bracket and suspended mounting.

Consult Installation Instructions on website for full details.

## SUPPLY

The enclosure unit is supplied complete with a wall bracket and ceiling mount clips to enable quick installation without

the need to perforate the housing. The unit is also fitted with an IP rated breather to equalise the internal temperature with the ambient to avoid build up of condensation inside.

**BR3-EXHS.WHT** White Weatherproof Exit Enclosure

## Contact

### Ecoglo International Limited

Unit 3, 160 Ferry Road, Waltham, Christchurch 8011  
PO Box 7698, Sydenham 8240, Christchurch, New Zealand

Phone: 03 348 3781 Fax: 03 343 6821

Email: [info@ecoglo.com](mailto:info@ecoglo.com) Web: [www.ecoglo.co.nz](http://www.ecoglo.co.nz)